


HARMONY



GLIDE



DOUBLE CHARGE 80x120 cm VITRIFIED TILES






ETHAN



GLAMOUR





DAZZLE



ZEUS







PARADISE









GLORY



CYRSTALLINE


















GARNET NERO










GARNET WHITE



GARNET CREMA




DOUBLE CHARGE 100x100 cm VITRIFIED TILES





SIMBA NERO



SIMBA COFFEE





SIMBA CREMA



SIMBA WHITE






DOUBLE CHARGE 100x100 cm VITRIFIED TILES





SANORA BEIGE



SANORA WHITE 20





SANORA GRIS




SANORA CHOCO











ZERO WHITE









JUANA CREMA



JUANA PEARL



























AIDEN



ALTAN



FLURRY















BLAISE THEO





COSMIC NERO COSMIC CHOCO












VOGUE FLAIR



SNOW ALLURE



MAJESTIC













ALBANO WHITE PLUS



ALBANO ROSSEL PLUS



ALBANO LEMON PLUS













SNOW FLAIR



SNOW VIRILE



ROSSEL
























MELANGE



CREMA FLURRY



MEGA WHITE



ROMANO



ROSSO VERONA



BELGIO











TRANCO



SAND MIAMI



SAND RIO



LUCIA













BRUN



HALO



RADO



GLAD



PANAROMA



SOVIET



DOUBLE CHARGE 60x60 cm VITRIFIED TILES











ADENA






SERENITY



TRANQUIL



ANTIQUE SAPPHIRE



KORREL



VIVA COTTA



SICILIA LEMON

DOUBLE CHARGE 60x60 cm VITRIFIED TILES





CARPO




SICILIA WHITE



NAPLES



NUVOLTA



FLAMING0



RIGATO





ALAINA



ACLIN



RIMINI




ACTON



ADAMA











60x60 cm I PEN





COLORS & S&P 60x60 cm VITRIFIED TILES PEN









S&P GREY





S&P RED

MANGO YELLOW

Technical Specifications

S. No.	Property	International Standard ISO 13006/EN14411 Group Bla Requirement	Johnson Marbonite Value	Test Method
	Dimensions & Surface Quality			
1	Deviation in Length & Width	± 0.6% or 2.0mm	± 0.2%	ISO 10545-2
2	Deviation in Thickness	± 5% or 0.5mm	± 4%	ISO 10545-2
3	Straightness of Sides	± 0.5% or 1.5mm	± 0.1%	ISO 10545-2
4	Rectangularity	± 0.5% or 2.0mm	± 0.2%	ISO 10545-2
5	Surface Flatness	± 0.5% or 2.0mm	± 0.2%	ISO 10545-2
6	Surface Quality	Min 95% Free from Visible Defects	>95% Free from Visible Defects	ISO 10545-2
	Physical Property			
7	Water Absorption	≤ 0.5%	≤ 0.05%	ISO 10545-3
8	Modulus of Rupture	≥ 35 N/mm²	≥ 38 N/mm²	ISO 10545-4
9	Breaking Strength	≥ 1300 N	≥ 1500 N	ISO 10545-4
10	Resistance to Deep Abrasion of Unglazed Tiles	≤ 175mm³	≤ 144mm³	ISO 10545-6
11	Resistance to Surface Abrasion of Glazed Tiles for Floor Application	Report Abrasion Class	Not Applicable	ISO 10545-7
12	Coefficient of Linear Thermal Expansion	Report Value	≤ 9 x 10 ⁻⁶ K ⁻¹	ISO 10545-8
13	Thermal Shock Resistance	Report Result	Resistant	ISO 10545-9
14	Crazing Resistance of Glazed Tiles	Report Result	Not Applicable	ISO 10545-11
15	Frost Resistance	Report Result	Resistant	ISO 10545-12
16	Moisture Expansion	Report Value	≤ 0.2 mm/m	ISO 10545-10
17	Small Color Differences - for plain colored tiles, where required in a specification	GL : △E<0.75 UGL : △E<0.75	UGL : △E<0.75	ISO 10545-16
18	Impact Resistance	Report Value	≥ 0.55	ISO 10545-5
19	Scratch Hardness of Surface (Moh's Scale)	Report Value	≥6	EN 101/DIN 18155
20	Slip Resistance for Floor Application	Report Value	0.30 - 0.45	ANSI B101.3
21	Bulk Density (g/cc)	Report Value	≥2	ASTM C373-16
	Chemical Property			
22	Resistance to Staining			
	- Glazed Tiles	Min Class 3	Not Applicable	ISO 10545-14
	- Unglazed Tiles	Report Resistance Class	Min Class 3	ISO 10545-14
23	Resistance to Chemicals			
а	Resistance to Low Concentrations of Acids and Alkalis			
	- Glazed Tiles	Report Resistance Class	Not Applicable	ISO 10545-13
	- Unglazed Tiles	Report Resistance Class	ULA	ISO 10545-13
b	Resistance to High Concentrations of Acids and Alkalis	Report Resistance Class	UHA	ISO 10545-13
С	Resistance to Household Chemicals and Swimming Pool Salts			
	- Glazed Tiles	GB	Not Applicable	ISO 10545-13
	- Unglazed Tiles	UB	UA	ISO 10545-13
24	Lead & Cadmium Release - for Glazed Tiles, where required	Report Value	Nil	ISO 10545-15
25	Color Resistance to UV light	Report Result	No Change in Color	DIN 51094

Packing Details

Product	Nominal Size (cm)	No of Tiles/Box	Approx Area/Box (sq m)	Approx Weight/Box (kgs)	Approx Cartons/ 20' Container	Approx Area per Container (sq m)
Marbonite 80x120	80x120	2	1.92	48.0	562	1079
Marbonite 100x100	100x100	2	2	51.5	524	1048
Marbonite 80x80	80x80	3	1.92	43.0	627	1204
Marbonite 60x60	60x60	4	1.44	29.5	915	1318




You can reach us at

Region	Branch	Tel.:
EAST	West Bengal (Kolkata)	033-22272128/29
	Odisha (Bhubaneshwar)	0674-6539836/6539837
	Ranchi	9798845560
	Siliguri	9836065812
	Guwahati	9127066591
WEST	Mumbai - Bandra to Dahanu	022 - 30647500/26547300
	Mumbai - Central	022 - 30647500/26547300
	Thane to Raigad	022 - 30246600
	Pune	020-41301164/31/61/63
	Ahmedabad	079-30072051/52/53/54/55
	Indore	0731-4007441
NORTH	Jalandhar	01824-505038/39
	Chandigarh	0172 - 4697100 / 4656940
	Delhi	011-49526600
	Jaipur	0141-2333922
	Ghaziabad	0120-4110377
	Lucknow	0522- 4025128/4065471/4026028
	Patna	0612-2254252
SOUTH	Bangalore	080-25446841/42/43/46
	Hyderabad	040-29802270/71/72
	Vijayawada	0866-2543616/17
	Vishakapatnam	0891-2796376
	Tirupathi	0877-3254151
	Chennai	044-28544116/28541881
	Coimbatore	0422-2540501/2548439
	Salem	0427-2280636/2280637/2280639
	Madurai	0452-4355584/4355594
	Tuticorin	0461-2271558/2278585
	Trichy	0431-2904730/40/50
	Ernakulam	0484-4098500/509/510
	Calicut	0495-2702505/2301474
	Trivandrum	0471-2551141

For address and contact numbers of our Johnson Exclusive Showrooms and Authorized Retailers, please visit our website www.hrjinida.com





Toll Free No.: 1800-22-7484 E-mail: customercare@hrjohnsonindia.com

For Export Enquiries, Email: export@hrjohnsonindia.com



H & R JOHNSON (INDIA)

(A Division of Prism Cement Limited)

Corporate Office: 7th Floor, Windsor, C. S. T. Road, Kalina, Santacruz (East), Mumbai - 400 098, India.

Download Johnson Tiles Mobile App

Registered Office: 305, Laxmi Niwas Apartments, Ameerpet, Hyderabad - 500016, India.

Contact branch for Pre laying services available for select products.

Colors shown are as accurate as the limitations of the printing process will allow. Prospective customers are advised to inspect a sample of the tile before ordering. Every effort has been made to ensure the accuracy of the information given. However, the company reserves the right to change the specifications without prior notice. Sometimes, variations in shade or size may occur which is inherent to the ceramic industry. Before fixing the tiles, we urge you to read and follow the fixing instructions given on the carton box of the tiles. The company will not take any $responsibility \ and \ will \ not \ accept \ any \ complaints \ of \ shade, size \ or \ planarity \ once \ the \ tiles \ have \ been \ fixed.$

Although every effort is made to ascertain that all the information provided in this brochure is accurate before printing, errors may still happen. Please contact the local branch office for updated information before placing orders. The information contained in this catalog is given in good faith. The Company takes no liability on account of any loss or damage either consequential or otherwise as a result of the information provided therein.

View our Tile informative videos





Google play

Scan this QR code to download Android version app





Scan this QR code to download iOS version app

